

The Lad-Saf™ flexible cable system consists of a top and bottom bracket that act as anchors for a steel cable that runs the length of the climbing area. A Lad-Saf™ sleeve connects the worker to the system, automatically follows the user during the climb and locks onto the cable in the event of a fall, allowing the user to regain their footing. Designed for ease of use, economy and versatility, optional brackets/designs are available for bolting or welding the system, choose rung clamp sizes/styles, choose systems for straight or curved ladders and for connection to wood, concrete or steel structures.



**Lad-Saf™ Specification**  
**Standard System**  
 6116280, 6110000,  
 6100400, 6160030,  
 6100090

**Safety System Options**

Part Number	Description	Price
6116280	Standard Top Bracket (up to 499')	★
6116410	Standard Top Bracket (over 500')	★
6110000	Cable Lifeline (last 3 digits in part# detail length example: 500' 6110500)	★
6100400	Cable Guide (up to 199')	★
6100515	Cable Guide (over 500')	★
6160030	Lad-Saf™ Flexible Cable Sleeve	★
6100090	Standard Bottom Bracket	★

**Harness Options**

1108176	DBI/SALA HARNESS DELTA FRONT/SIDE/BACK D RINGS TONGUE BUCKLE LG STRAPS SIZE LARGE	★
1102010 BC#791870	DBI/SALA HARNESS DELTA CROSS OVER FRONT/ BACK D RINGS PASS THROUGH BUCKLE LEG STRAPS SIZE UNIVERSAL	★
1107800	DBI/SALA HARNESS DELTA FRONT/BACK D RINGS TONGUE BUCKLE LEG STRAPS LOOPS FOR BELT SIZE LARGE	★
1108526 BC#413965	DBI/SALA HARNESS EXOFIT FRONT/BACK D RINGS QUICK CONNECT BUCKLES LOOPS FOR BELT SIZE MEDIUM	★

LAD-SAF™ FLEXIBLE CABLE LADDER SAFETY SYSTEM