

FLANGES - ROUND, SQUARE, ANGLE & FLAT

FLANGES - ROUND, SQUARE, ANGLE & FLAT



LIGHT ANGLE FLANGE RINGS

SIZE	PRICE
8" 1-1/4"x1/8"	★
10" 1-1/4"x1/8"	★

HEAVY ANGLE FLANGE

SIZE	PRICE
16" 1-3/4"x3/16"	★
18" 1-3/4"x3/16"	★
20" 1-3/4"x3/16"	★
22" 1-3/4"x3/16"	★
24" 1-3/4"x3/16"	★



PIPE SIZE FLANGE RINGS

SIZE	Flat Flange	Angle Iron
6-5/8" 1-1/4"x3/16"	★	★
8-5/8" 1-1/4"x3/16"	★	★
10-3/4" 1-1/2"x3/16"	★	★
12-3/4" 1-1/2"x3/16"	★	★



FLAT FLANGE RINGS

SIZE	PRICE
6" 1-1/4"x3/16"	★
8" 1-1/4"x3/16"	★
10" 1-1/4"x3/16"	★
12" 1-1/2"x3/16"	★
14" 1-1/2"x3/16"	★
16" 1-1/2"x3/16"	★
18" 1-1/2"x3/16"	★
20" 1-1/2"x3/16"	★
22" 1-1/2"x3/16"	★
24" 1-1/2"x3/16"	★

ANGLE FLANGE RINGS

NATIONAL STANDARD PUNCHED

DIA	MATERIAL	PRICE	GALVANIZED
3"	10ga. PRESSED ANGLE	★	
4"		★	
5"		★	
6"	1 1/4" x 1 1/4" x 1/8"	★	★
7"	1 1/4" x 1 1/4" x 3/16" ROLLED ANGLE	Call	
8"		★	★
9"		Call	
10"		★	★
11"		Call	
12"	1 1/2" x 1 1/2" x 3/16" ROLLED ANGLE	★	★
13"		Call	
14"		★	★
15"		Call	
16"		★	★
17"		Call	
18"		★	★
19"		Call	
20"		★	
21"		Call	
22"		★	
23"		Call	
24"	★		
25"	2" x 2" x 3/16" ROLLED ANGLE	Call	
26"		★	
27"		Call	
28"		★	
29"		Call	
30"		★	



SQUARE FLANGES

SIZE	Flat Flanges Carbon Steel	Flat Flanges Galvanized	Angle Iron Carbon Steel	Angle Iron Galvanized
6" 1-1/4"x3/16"	★	★	★	★
8" 1-1/4"x3/16"	★	★	★	★
10" 1-1/4"x3/16"	★	★	★	★
12" 1-1/2"x3/16"	★	★	★	★
14" 1-1/2"x3/16"	★	★	★	★
16" 1-1/2"x3/16"	★	★	★	★
18" 1-1/2"x3/16"	★	★	★	★
20" 1-1/2"x3/16"	★	★	★	★
22" 1-1/2"x3/16"	★	★	★	★
24" 1-1/2"x3/16"	★	★	★	★
26" 2"x3/16"	★	★	★	★
28" 2"x3/16"	★	★	★	★
30" 2"x3/16"	★	★	★	★

Z.R.C. GALVANIZING PAINT



**GENERAL PROPERTIES:** ZRC® is a high-quality cold galvanizing compound based on a trade secret organic binder which affords true galvanic anti-corrosion protection to metals. The dried film of ZRC is 95% metallic zinc. Because of the uniqueness of the formulation, ZRC is the only coating of its type to be recognized under the Component Program of Underwriter's Laboratories, Inc.

**RECOMMENDED USES:** ZRC is widely used without topcoat in place of hot-dip galvanizing. Also used as a high-performance base coat with a variety of topcoats. Used for repair of damaged hot-dip galvanizing Galvalume® and zinc metallizing, reglvanizing worn hot-dip galvanizing, repair of weldments, and repair of damaged inorganic zinc coatings. Excellent for long-term protection of structural steel, water and waste facilities, power plants, transmission towers and antennae, steel decking and bridges, and numerous OEM uses.

SEE PAGE 16 FOR STAINLESS STEEL PRICING AND PAGE 32 FOR DIMENSIONAL INFORMATION.  
CONTACT PREMIER COMPONENTS FOR GALVANIZED PRICING NOT SHOWN.