


**SQUARE SPOUTING  
SEAM WELDED STYLE  
SQUARE SPOUTING**



SIZE	PRICE PER 10' SECTION - INCLUDES PRIMED FINISH							
	12ga. Unflanged	12ga. Flanged	10ga. Unflanged	10ga. Flanged	7ga. Unflanged	7ga. Flanged	1/4" Unflanged	1/4" Flanged
6"	☉	☉	☉	☉	☉	☉	☉	☉
8"	☉	☉	☉	☉	☉	☉	☉	☉
10"	☉	☉	☉	☉	☉	☉	☉	☉
12"	☉	☉	☉	☉	☉	☉	☉	☉
14"	☉	☉	☉	☉	☉	☉	☉	☉
16"	☉	☉	☉	☉	☉	☉	☉	☉
18"	☉	☉	☉	☉	☉	☉	☉	☉
20"	☉	☉	☉	☉	☉	☉	☉	☉
22"	10 ga.	10 ga.	☉	☉	☉	☉	☉	☉
24"	10 ga.	10 ga.	☉	☉	☉	☉	☉	☉
30"	10 ga.	10 ga.	☉	☉	☉	☉	☉	☉
36"	10 ga.	10 ga.	☉	☉	☉	☉	☉	☉

PLEASE CALL PREMIER FOR SHORTER SPOUT SECTIONS AND SIZES NOT LISTED.  
ADD 20% FOR 10ga. & 7ga. GALVANIZED SEAM WELDED / 30% for 1/4" Wall



**REMOVABLE LID STYLE  
SQUARE SPOUTING**

SIZE	PRICE PER 10' SECTION - INCLUDES PRIMED FINISH (EXCEPT GALVANIZED)									
	Unlined	HD-7ga. AR lined	1/4" Urethane Blue	5/16" Urethane Blue	1/4" High Energy Orange	5/16" High Energy Orange	1/4" Kryptane Red	5/16" Kryptane Red	1/4" Ceramic Tile	Add for Galvanized
6" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
8" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
10" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
12" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
14" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
16" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-16" (7ga.)	★	★	★	★	★	★	★	★	★	★
18" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-18" (7ga.)	★	★	★	★	★	★	★	★	★	★
20" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-20" (7ga.)	★	★	★	★	★	★	★	★	★	★
22" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-22" (7ga.)	★	★	★	★	★	★	★	★	★	★
24" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-24" (7ga.)	★	★	★	★	★	★	★	★	★	★
30" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-30" (7ga.)	★	★	★	★	★	★	★	★	★	★
36" x 10ga.	☉	☉	☉	☉	☉	☉	☉	☉	☉	☉
HD-36" (7ga.)	★	★	★	★	★	★	★	★	★	★

HD (Heavy Duty) 7ga. body spouts include 7 ga. Lids. 6" -14" Spouts will utilize 1/4" thick flanges and 16" - 36" Spouts will utilize 3/8" thick flanges. All flanges will be punched per Square Spout flange punching pattern shown on page 32 with added holes for strength. All Spouts have a 10" wide brace on the top at each end for added strength.

PLEASE CALL THE FACTORY FOR SHORTER SPOUT SECTIONS AND CUSTOM SIZES NOT LISTED ABOVE.

ALL LINED SPOUTS INCLUDE FULL WIDTH BOTTOM AND 2/3 OF EACH SIDE. SPECIAL 4-SIDED LINING IS AVAILABLE. AR LINERS ARE PLUG WELDED IN PLACE AND URETHANE LINERS ARE INSTALLED WITH ZINC PLATED ELEVATOR BOLTS.

**SQUARE SPOUTING CAPACITY APPROXIMATIONS**

SIZE	SQR IN	BPH	SIZE	SQR IN	BPH	SIZE	SQR IN	BPH	SIZE	SQR IN	BPH
6"	36	2,200	12"	144	10,000	18"	324	22,500	24"	576	40,000
8"	64	4,400	14"	196	13,500	20"	400	28,000	30"	900	63,000
10"	100	7,000	16"	256	17,500	22"	484	33,500	36"	1296	90,000

CONTACT PREMIER COMPONENTS FOR STAINLESS STEEL PRICING.

SEE PAGE 28 FOR SPOUT VELOCITY RECOMMENDATIONS.

www.premier-com.com

877-681-3064