



**STANDARD FEATURES**

- 3/16" PL inner spout
- Flanged and bolted inner spout for removal through inspection door
- Inner spout enters discharge stub
- Locking ring for positive spout positioning
- Replaceable inlet stub
- Inspection door
- 10ga. discharge stubs flanged

**AVAILABLE CONFIGURATIONS**

- 6" up to 24" round spout
- 45° and 60°
- Flat back and full round
- AR steel liners
- Urethane liners
- Hot dip galvanized
- Stainless steel construction



FB: FLAT BACK (SHOWN)

**SUPERIOR ALIGNMENT FOR LEAK FREE OPERATION**

Our distributor inner spouts are positively aligned with discharge stubs using a locator ring with alignment slots for each outlet. The inner spout enters the discharge stub as it is lowered into the locator ring. The inner spout entry into the discharge stub, combined with the inner spout seal, provides leak free operation, even in a choked spout situation. The locator ring prevents the inner spout from dropping down, until it is aligned with the discharge stub. This prevents "partial alignment" of the inner spout and discharge stub. Both manual and electric distributors utilize the same alignment process.



**INDICATE FULL ROUND (FR) OR FLAT BACK (FB)**

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
6	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
8	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
10	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
12	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
14	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

SIZE	# Ducts	FR/FB	45° PAINTED	45° GALVANIZED	60° PAINTED	60° GALVANIZED
16	4	FR or FB	☉	☉	☉	☉
	6	FR or FB	☉	☉	☉	☉
	8	FR or FB	☉	☉	☉	☉
	10	FR or FB	☉	☉	☉	☉
	12	FR or FB	☉	☉	☉	☉
	14	FR	PLEASE CALL FOR PRICING			
	16	FR	PLEASE CALL FOR PRICING			
	18	FR	PLEASE CALL FOR PRICING			

**CONTACT PREMIER FOR DISTRIBUTOR CONFIGURATIONS NOT LISTED ABOVE**

Pricing reflects pipe or cable control operation. See page 27 for available power options. See page 28 for dimensional information.

Contact Premier for stainless steel construction.

**DISTRIBUTOR LINING OPTIONS:**

- Add 20% for 10ga. AR Steel or 1/4" Blue Urethane for Inner Spout lining only
- Add 35% for 10ga. AR Steel or 1/4" Blue Urethane for lining Inner Spout and Discharge Stubs
- Add 55% for 1/4" Ceramic Tile lining for Inner Spout and Discharge Stubs

CONTACT PREMIER COMPONENTS FOR SWING-FLO DISTRIBUTOR PRICING AND SPECIFICATIONS. SEE PAGE 28 FOR DIMENSIONS AND SPECIFICATIONS OF FULL ROUND AND FLATBACK DISTRIBUTORS