

**3M™ DBI-SALA® Lad-Saf™
FLEXIBLE CABLE
VERTICAL SAFETY SYSTEMS**



SAFETY SYSTEM OPTION 1

(INCLUDES CHOICE OF TOP & BOTTOM BRACKET SYSTEM, PRE-SWAGED CABLE AND CABLE GUIDES)

TOP & BOTTOM BRACKET SYSTEM (BOTH BRACKETS INCLUDED)

APPLICATION	USER	MATERIAL	PART#	PRICE EACH
RUNG	2 USER	GALVANIZED STEEL	6116612	⊕
RUNG	2 USER	STAINLESS STEEL	6116613	⊕
RUNG	4 USER	GALVANIZED STEEL	6116614	⊕
WOOD POLE	2 USER	GALVANIZED STEEL	6116616	⊕
MONOPOLE	4 USER	GALVANIZED STEEL	6116615	⊕
MONOPOLE	4 USER	STAINLESS STEEL	6116619	⊕
CLIMB EXTENSION	2 USER	GALVANIZED STEEL	6116617	⊕
TELESCOPING EXTENSION	4 USER	GALVANIZED STEEL	6116618	⊕



PRE-SWAGED CABLE AT DESIRED LENGTH (PRICE FOR 10' SECTION SHOWN - PART # (6104010, 6105010, 6106010 & 6107010))

PART#	6104XXX	6105XXX	6106XXX	6107XXX
DIAMETER	3/8" (9.5mm)	3/8" (9.5mm)	3/8" (9.5mm)	3/8" (9.5mm)
STRAND	1x7	1x7	7x19	7x19
STEEL	GALVANIZED	STAINLESS	GALVANIZED	STAINLESS
PREFORMED	LEFT, REGULAR LAY	LEFT, REGULAR LAY	RIGHT, REGULAR LAY	RIGHT, REGULAR LAY
COMPLIANCE	RR-W-410	RR-W-410	RR-W-410	RR-W-410
BREAKING STRENGTH	15,400 lbs. MINIMUM	18,000 lbs. MINIMUM	14,400 lbs. MINIMUM	12,000 lbs. MINIMUM
LAST THREE OF PART# XXX = (010)	\$ / 10' SECTION	\$ / 10' SECTION	\$ / 10' SECTION	\$ / 10' SECTION

FIRST 4 NUMBERS OF THE PART# REPRESENT THE CABLE TYPE AND THE LAST 3 NUMBERS REPRESENT THE CABLE LENGTH IN FEET DESIRED.

TAKE DESIRED LENGTH, DIVIDE BY 10 AND MULTIPLY BY COST PER 10' SECTION.

CABLE GUIDES - RECOMMENDED EVERY 20-40 FEET

APPLICATION(S)	TYPE	MATERIAL	PART #	PRICE EACH
LADDER	STRAIGHT GUIDE	GALVANIZED STEEL	6100400	⊕
LADDER	STRAIGHT GUIDE	STAINLESS STEEL	6100457	⊕
LADDER	L GUIDE	STAINLESS STEEL	6100513	⊕
LADDER	STRAIGHT GUIDE	GALVANIZED STEEL	6100530	⊕
TELESCOPING & EXTENSION	STRAIGHT GUIDE	STAINLESS STEEL	6100401	⊕
MONOPOLE	L GUIDE	GALVANIZED STEEL	6100515	⊕
WOOD POLE	STRAIGHT GUIDE	STAINLESS STEEL	6100140	⊕

HOLLOW RUNG LADDER SUPPORTS MAY BE REQUIRED FOR ADDITIONAL SUPPORT.
CONTACT PREMIER COMPONENTS FOR MORE INFORMATION.



6160054 DBI-SALA CABLE SLEEVE X3 3/8" DETACHABLE W/ CARABINER ⊕

SAFETY SYSTEM KIT OPTION 2 (2-USER LADDER SYSTEM AND CABLE)

CABLE LENGTH	20 ft	30 ft	40 ft	50 ft	60 ft	70 ft	80 ft	90 ft	100 ft
# OF GUIDES INCLUDED	0	1	1	1	2	2	2	3	3
GALVANIZED STEEL: 6116612 RUNG, 2 USER 6104XXX: 1X7 SWAGED 3/8" 6100400: CABLE GUIDE FOR FIXED LADDER - 1 PER 30'	6118020	6118030	6118040	6118050	6118060	6118070	6118080	6118090	6118100
PRICE EACH	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕
STAINLESS STEEL: 6116613 RUNG, 2 USER 6105XXX: 1X7 SWAGED 3/8" 6100457: CABLE GUIDE FOR FIXED LADDER - 1 PER 30'	6119020	6119030	6119040	6119050	6119060	6119070	6119080	6119090	6119100
PRICE EACH	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕	⊕



1102950 DBI SALA HARNESS FRONT/BACK D RINGS, TONGUE BUCKLE LEG STRAPS UNIVERSAL SIZE ⊕

LAD-SAF™ FLEXIBLE CABLE LADDER SAFETY SYSTEM