

BIN PRESSURE RELIEF VENTS



Available in two sizes

8 Inch Diameter ★

14 Inch Diameter ★



Easy installation with no tools or welding required. Improves the flow of product by reducing pressure build up. Install with cloth filter and cover.

DUST SOCKS

Rubber Coated Nylon (RCN)

Very pliable soft rubber coating on a two-way nylon backing. The rubber portion of the rubber coated nylon fabric is in compliance with FDA requirements of CFR 21.177.2600 (Rubber Articles Intended for Repeated Use).

Fiber Content Neoprene with nylon backing

Material is rubber coated nylon



WEIGHT 32 OUNCES/YD2 / 678 G/M2

PERMEABILITY 0 CFM @ 0.5 WATER GAUGE

TEMPERATURE RANGE

0° TO 200° F CONTINUOUS, 250° F MAX -18°

TO 93° C CONTINUOUS, 121° C MAX



ROUND & SQUARE FLEXIBLE CONNECTORS



ROUND	EACH
6"	★
8"	★
10"	★
12"	★
14"	★
16"	★
18"	★
20"	★
24"	★

SQUARE	EACH
6"	★
8"	★
10"	★
12"	★
14"	★
16"	★
18"	★
20"	★
24"	★



6" through 24" diameter available 12" length.