

ROUND SPOUTING

PREMIER COMPONENTS SPOUTING IS FIRST RUN MATERIAL - NO SECONDS!

ALL SPOUTING IS AVAILABLE IN 20' OR 40' LENGTHS.

Premier Components, Inc. has the best spouting and accessory prices in the industry. Contact us for

GALVANIZED ROUND SPOUTING

SIZE	PRICE PER FOOT						
	14ga.	12ga.	11ga.	10ga.	7ga.	1/4"	.219"
4"	*	*					
5"	*	*					
6"	*	*		*	*		
8"	*	*	*	*	*	*	
10"		*	*	*	*	*	
12"		*		*	*	*	
14"				*	*	*	*
16"				*	*	*	
18"						*	
20"						*	
24"						Call	

PLEASE CALL FOR PRICING ON HIGHLIGHTED SIZES

CARBON STEEL ROUND SPOUTING

SIZE	PRICE PER FOOT						
	14ga.	12ga.	11ga.	10ga.	7ga.	1/4"	.219"
4"	Call	Call		*			
5"	Call	Call		Call			
6"	Call	Call	Call	*	*		
8"	Call	Call	Call	*	*	*	
10"			Call	*	*	*	
12"		Call		*	*	*	
14"		Call		*	*	*	*
16"		Call		*	*	*	
18"						*	
20"						*	
24"						Call	

PLEASE CALL FOR PRICING ON HIGHLIGHTED SIZES

STAINLESS STEEL SPOUTING

SIZE	PRICE PER FOOT			
	14ga.	12ga.	11ga.	10ga.
4"	Call	Call		Call
6"	Call	Call	*	Call
8"	Call	Call	*	*
10"	Call	Call	*	*
12"	Call	Call	*	Call
14"		Call		*
16"		Call		*



SEE PAGE 16 FOR STAINLESS STEEL ACCESSORIES



PRICES SUBJECT TO CHANGE GIVEN VOLATILITY OF STEEL PRICES AND CURRENT INVENTORY LEVELS.



TUFF-TUBE SPOUT LINERS



Tuff-Tube is an innovative, wear-resistant, seamless, polyurethane spout liner that comes in any size diameter, up to 20' lengths for new or existing spouting applications. This exciting new product is a replacement slip-in urethane liner that counters material wear to spout lining—saving time and money and extending useful life of equipment by reducing down time. Worn liner can be rotated 120° - 180° to present additional wear surface. Completely used liner can be removed and replaced using the same spout. Contact Premier Components for pricing, availability and further specifications.

ROUND SPOUTING CAPACITY APPROXIMATIONS		
SIZE	in ²	BPH
6"	28.3	1,960
8"	50.3	3,500
10"	78.5	5,460
12"	113.1	7,910
14"	154.0	10,780
16"	201.1	14,000
18"	254.5	17,780
20"	314.2	21,980
24"	452.3	31,500

SIDEWALL THICKNESS
14ga. = 0.0747"
12ga. = 0.1046"
11ga. = 0.125"
10ga. = 0.1345"
7ga. = 0.1793"
1/4" = 0.25"

O.D. SIZE	ROUND SPOUTING WEIGHTS POUNDS PER LINEAL FOOT					
	14ga.	12ga.	11ga.	10ga.	7ga.	1/4"
4"	3.2	4.5		5.7		
5"	4.0	5.6		7.2		
6"	4.8	6.8		8.6	11.6	15.3
6-5/8"				9.6		
7"		7.9		10.1		
8"	6.5	9.0	10.3	11.6	15.6	20.7
8-5/8"				12.1	16.9	
10"		11.3	12.8	14.5	19.7	26.0
10-3/4"				15.6	21.2	
12"		13.3		17.5	23.7	31.4
12-3/4"				18.6	25.2	
14"		15.9		20.4	27.7	36.7
16"		18.2		23.4	31.7	42.1
18"						48.0
20"						53.0
24"						64.0

SEE PAGE 28 FOR SPOUT VELOCITY RECOMMENDATIONS.