

**MOTOR/GEARBOX SLIDE GATE DRIVE OPTIONS**

MOTOR/GEARBOX DRIVES (PROXIMITY STYLE LIMIT SWITCHES INCLUDED)			FACTORY MOUNTED	SUPPLIED LOOSE
1/2 hp, TEFC	RA GEARBOX	1 PH / 110V	★	★
1/2 hp, X-PRF	RA GEARBOX	1 PH / 110V	★	★
1/2 hp, TEFC	RA GEARBOX	3 PH / 230-460V	★	★
1/2 hp, X-PRF	RA GEARBOX	3 PH / 230-460V	★	★
1/2 hp, TEFC	RA GEARBOX	3 PH / 575V	★	★
1/2 hp, X-PRF	RA GEARBOX	3 PH / 575V	★	★

**ADD PRICE OF MANUAL SLIDE GATE TO COST OF SELECTED MOTOR/GEARBOX COMBO**



ADD AN EXTERNAL MOUNT POTENTIOMETER (PERCENTAGE OPEN / CLOSE)		PRICE
	FITS ANY SIZE GATE	★
	EXTERNALLY MOUNTED POTENTIOMETER	★
	POTENTIOMETER SHIPPED LOOSE	★
POTENTIOMETER REMOTE DISPLAY W/DUAL RELAYS		★

A POTENTIOMETER WILL ALLOW ELECTRIC OPERATED GATES TO BE POSITIONED ANYWHERE FROM FULLY OPENED TO FULLY CLOSED.

ADD PRICE OF MANUAL SLIDE GATE TO COST OF POTENTIOMETER

POTENTIOMETER MOUNTING ADAPTER SLEEVE		PRICE
	Potentiometer mounting adapter sleeves are used for mounting a potentiometer to an existing (non-tapped) gate with a 1" control shaft.	★

★ 6" & 8": MICRO SWITCH REQUIRED FOR BOTH AIR & MOTOR. 10", 12" & 14": MICRO SWITCH REQUIRED FOR AIR DRIVE ONLY.

**AIR ACTUATED (PNEUMATIC OPERATED) COMPONENTS - 90 psi minimum**

		SUPPLIED LOOSE	INSTALLATION
<b>SINGLE SOLENOID</b> (GATE CLOSSES AT POWER LOSS)	WEATHERTIGHT CONSTRUCTION (120 VAC or 24 VDC)	★	★ TO INSTALL PNEUMATIC COMPONENTS ON SLIDE GATES
	EXPLOSION PROOF CONSTRUCTION	★	
<b>DOUBLE SOLENOID</b> (GATE HOLDS POSITION AT POWER LOSS)	WEATHERTIGHT CONSTRUCTION (120 VAC or 24 VDC)	★	
	EXPLOSION PROOF CONSTRUCTION	★	
★ GO LIMIT SWITCHES (OPTIONAL)		★	

CYLINDER (TRAVEL)	PRICE
6" AIR CYLINDER	★
8" AIR CYLINDER	★
10" AIR CYLINDER	★
12" AIR CYLINDER	★
14" AIR CYLINDER	★
16" AIR CYLINDER	★
18" AIR CYLINDER	★
20" AIR CYLINDER	★
22" AIR CYLINDER	★
24" AIR CYLINDER	★
26" AIR CYLINDER	★
28" AIR CYLINDER	★
30" AIR CYLINDER	★
32" AIR CYLINDER	★
34" AIR CYLINDER	★
36" AIR CYLINDER	★

AIR ACTUATED SLIDE GATES SPEED CAN BE VARIED BASE ON PSI AND ADJUSTMENT OF MUFFLERS.



ADD PRICE OF SLIDE GATE TO COST OF APPROPRIATE AIR CYLINDER, SELECTED SOLENOID(S), AND LIMIT SWITCHES.

**ANDCO EAGLE ACTUATOR SLIDE GATE DRIVES**

PREMIER COMPONENTS STOCKS ANDCO ACTUATORS



ANDCO ACTUATORS OPERATE UP TO 2" PER SEC. STANDARD SPEED IS .8" PER SEC.

**ANDCO EAGLE ACTUATOR PRICING (NON-MOUNTED)**

INCLUDES FACE / FLANGE MOUNT FOR SLIDE GATE MOUNTING.

ACTUATOR STROKE LENGTH	STANDARD ACTUATOR	ACTUATOR W/ POTENTIOMETER
UP TO 6"	★	★
UP TO 12"	★	★
UP TO 18"	★	★
UP TO 24"	★	★
UP TO 30"	★	★
UP TO 36"	★	★

**ANDCO EAGLE ACTUATOR PRICING (FACTORY INSTALLED)**

ACTUATOR STROKE LENGTH	STANDARD ACTUATOR	ACTUATOR W/ BUILT-IN POTENTIOMETER
UP TO 6"	★	★
UP TO 12"	★	★
UP TO 18"	★	★
UP TO 24"	★	★
UP TO 30"	★	★
UP TO 36"	★	★

POTENTIOMETER OPTIONS ARE BUILT INTO UNITS

ADD PRICE OF SELECTED ANDCO-READY GATE TO THE ABOVE

ANDCO ACTUATORS ARE 1 PH/120V AND COME WITH; (2) BUILT-IN LIMIT SWITCHES, FACE FLANGE MOUNTING BRACKET AND EXPLOSION PROOF ENCLOSURE.

SLIDE GATE DRIVES