




BlueLevel Technologies Rotary Paddle Power Units			
MODEL	VOLTAGE	DESCRIPTION	PRICE
40-1111-111	115VAC	Ordinary location point level indicator with aluminum screw-off cover and housing, dual 3/4"NPT conduit ports, 1-1/4"NPT process port thread, FDA compliant powder coat finish, DPDT relay output rated to 8A at 250VAC, plug-in terminal strips and high intensity indicator lights standard. Fail-safe output, high/low selectable, on power failure.	☛
40-1211-111	230VAC		☛
40-1411-111	12VDC		☛
40-1511-111	24VDC		☛
40-1311-111	24VAC		☛
40-1121-111	115VAC	Hazardous Location point level indicator with screw-off cover, no visible indicator lights, conforms to UL; Class I Groups C & D, and Class II Groups E, F, & G. FDA compliant powder coated aluminum housing with dual 3/4"NPT conduit ports and a 1-1/4"NPT process port, DPDT relay output rated to 8A at 250VAC, plug-in terminal strips, and fail safe output: High/Low selectable on power failure.	☛
40-1221-111	230VAC		☛
40-1421-111	12VDC		☛
40-1521-111	24VDC		☛
40-1321-111	24VAC		☛

BlueLevel Technologies Shaft Couplers		
MODEL	DESCRIPTION	PRICE
410013	Standard threaded shaft coupling, accepts BlueLevel and most BinMaster and Monitor brand threaded paddles.	☛
410014	Shaft coupling for use with Binicator and most Ktek and Conveyor Component brand paddles.	☛
410002	Flexible shaft coupling, for use in top mount applications with solid extension shafts.	☛
410021	Extension shaft coupling for use with folding paddles.	☛
410022	Extension shaft coupling for use with threaded paddles.	☛

BlueLevel Technologies Side Mounting Plate Kits		
MODEL	DESCRIPTION	PRICE
410012	Ø8" flat, round mounting plate kit, powder coated cold rolled steel with 1/4"NPT half-coupling and neoprene gasket.	☛
410012-01	Similar kit to above except constructed from 304 grade stainless steel, with neoprene gasket.	☛
410012-03	Wide 4.0" corrugated steel mounting plate kit with 1-1/4"NPT half-coupling welded in place, galvanized.	☛
410012-04	Narrow 2.66" corrugated steel mounting plate kit with 1-1/4"NPT half-coupling welded in place, galvanized.	☛

BlueLevel Technologies Top Mounting Plate Kits		
MODEL	DESCRIPTION	PRICE
410011	Ø8" flat, round mounting plate kit, powder coated cold rolled steel with 1/4"NPT full-coupling, with neoprene gasket.	☛
410011-01	Similar kit to above but constructed with 304 stainless steel, includes neoprene gasket.	☛

BlueLevel Technologies Rotary Paddles		
MODEL	DESCRIPTION	PRICE
410003	Double-vane stainless steel folding paddle, inserts through a 1-1/4" NPT coupler, slides over and pins directly to the indicator shaft. No threaded coupler is needed. Good for approximately 40-90 lbs/ft³ bulk density material.	☛
410000	Standard fixed 3-vane threaded paddle, 5" diameter, stainless steel construction. Good for approximately 30-100lbs/ft³ bulk density material.	☛
410004	Single-vane stainless steel folding paddle, inserts through a 1-1/4"NPT coupler, slides over and pins directly to the indicator shaft. No threaded coupler is needed. Good for approximately 40-90 lbs/ft³ bulk density material.	☛
410001	Large tri-vane 7" diameter stainless steel threaded paddle, good for approximately 5-40 lbs/ft³ bulk density material.	☛
410015	"Banana" style threaded paddle, stainless steel, inserts through 1-1/4"NPT coupler, good for approximately 30-70 lbs/ft³ bulk density material.	☛
410016	Single-vane heavy duty stainless steel threaded paddle, inserts through 1-1/4"NPT coupler, good for bulk densities of 50 lbs/ft³ and up.	☛
410019	Double-vane heavy duty stainless steel threaded paddle, good for bulk densities of 40 lbs/ft³ and up.	☛
410020	Four-vane heavy duty stainless steel threaded paddle, good for bulk densities of 30 lbs/ft³ and up.	☛



1/4" SCHEDULE 40 GALVANIZED PIPE GUARDS		
MODEL	LENGTH	PRICE
410009-012	12"	☛
410009-024	24"	☛
410009-036	36"	☛
410009-048	48"	☛
410009-060	60"	Discontinued
410009-072	72"	☛

1/4" SCHEDULE 40, 304 STAINLESS STEEL PIPE GUARDS		
MODEL	LENGTH	PRICE
410010-012	12"	☛
410010-024	24"	☛
410010-036	36"	☛
410010-048	48"	☛
410010-060	60"	☛
410010-072	72"	☛


BlueLevel Technologies Shaft Guard Pipe Couplings		
MODEL	DESCRIPTION	PRICE
410017	1/4" Galvanized Steel Pipe Coupler	☛
410018	1/4" Stainless Steel Pipe Coupler	☛

BlueLevel Technologies Top Mount Folding Paddle Shaft Extensions		
GALVANIZED SHAFT		
MODEL	LENGTH	PRICE
410007-012C	12"	☛
410007-024C	24"	☛
410007-036C	36"	☛
410007-048C	48"	☛
410007-060C	60"	☛
410007-072C	72"	☛

304 STAINLESS STEEL SHAFT		
MODEL	LENGTH	PRICE
410008-012C	12"	☛
410008-024C	24"	☛
410008-036C	36"	☛
410008-048C	48"	☛
410008-060C	60"	☛
410008-072C	72"	☛

BlueLevel Technologies Top Mount Threaded Paddle Shaft Extensions		
GALVANIZED SHAFT		
MODEL	LENGTH	PRICE
410007-012	12"	☛
410007-024	24"	☛
410007-036	36"	☛
410007-048	48"	☛
410007-060	60"	☛
410007-072	72"	☛

304 STAINLESS STEEL SHAFT		
MODEL	LENGTH	PRICE
410008-012	12"	☛
410008-024	24"	☛
410008-036	36"	☛
410008-048	48"	☛
410008-060	60"	☛
410008-072	72"	☛



- Important Notes for Shaft Extensions:**
- Guard not required if shaft extension is 24" or less
  - Minimum guard length is 6 inches.
  - Minimum shaft extension length is 6 inches.
  - Maximum single piece length is 72 inches.
  - Maximum total length is 144 inches.
  - Extension and/or guard lengths exceeding 72 inches must be ordered in multiple sections.
  - All shaft extensions are supplied with 1/4" NPSC coupling unless the part number ends in \_\_\_C.
  - When joining shaft guard sections, order the appropriate galv. or stainless 1/4" NPSC coupling.

PLEASE CONTACT PREMIER COMPONENTS FOR CUSTOM SHAFT EXTENSIONS AND GUARDS.