

SQUARE SPOUTING

SEAM WELDED STYLE
SQUARE SPOUTING

SIZE	PRICE PER 10' SECTION - INCLUDES PRIMED FINISH							
	12ga. Unflanged	12ga. Flanged	10ga. Unflanged	10ga. Flanged	7ga. Unflanged	7ga. Flanged	1/4" Unflanged	1/4" Flanged
6"	☆	☆	☆	☆	☆	☆	☆	☆
8"	☆	☆	☆	☆	☆	☆	☆	☆
10"	☆	☆	☆	☆	☆	☆	☆	☆
12"	☆	☆	☆	☆	☆	☆	☆	☆
14"	☆	☆	☆	☆	☆	☆	☆	☆
16"	☆	☆	☆	☆	☆	☆	☆	☆
18"	☆	☆	☆	☆	☆	☆	☆	☆
20"	☆	☆	☆	☆	☆	☆	☆	☆
22"	10 ga.	10 ga.	☆	☆	☆	☆	☆	☆
24"	10 ga.	10 ga.	☆	☆	☆	☆	☆	☆
30"	10 ga.	10 ga.	☆	☆	☆	☆	☆	☆
36"	10 ga.	10 ga.	☆	☆	☆	☆	☆	☆

PLEASE CALL PREMIER FOR SHORTER SPOUT SECTIONS AND SIZES NOT LISTED.
ADD 20% FOR 10ga. & 7ga. GALVANIZED SEAM WELDED / 30% for 1/4" Wall

HD (Heavy Duty) 7ga. Body include 7ga. lids. All flanges will be punched per HD Square Spout flange punching pattern shown on page 32 with added holes for strength. All square spouts have extended bracing on the top and ends for added strength along with heavy duty square flanges.

REMOVABLE LID STYLE
SQUARE SPOUTING

SIZE	PRICE PER 10' SECTION - INCLUDES PRIMED FINISH (EXCEPT GALVANIZED)									
	Unlined	HD-7ga. AR lined	1/4" Urethane Blue	5/16" Urethane Blue	1/4" High Energy Orange	5/16" High Energy Orange	1/4" Kryptane Red	5/16" Kryptane Red	1/4" Ceramic Tile	Add for Galvanized
6" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
8" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
10" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
12" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
14" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
16" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-16" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
18" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-18" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
20" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-20" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
22" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-22" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
24" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-24" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
30" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-30" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
36" x 10ga.	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆
HD-36" (7ga.)	☆	☆	☆	☆	☆	☆	☆	☆	☆	☆

6", 8" and 10" are manufactured with 1 1/4" x 1 1/4" x 1/4" flanges
12" - 24" are manufactured with 1 1/2" x 1 1/2" x 3/8" flanges
26" and larger are manufactured with 2" x 2" x 3/8" flanges

PLEASE CALL THE FACTORY FOR SHORTER SPOUT SECTIONS AND CUSTOM SIZES NOT LISTED ABOVE.
ALL LINED SPOUTS INCLUDE FULL WIDTH BOTTOM AND 2/3 OF EACH SIDE. SPECIAL 4-SIDED LINING IS AVAILABLE.
AR LINERS ARE PLUG WELDED IN PLACE AND URETHANE LINERS ARE INSTALLED WITH ZINC PLATED ELEVATOR BOLTS.

SQUARE SPOUTING CAPACITY APPROXIMATIONS

SIZE	SQR IN	BPH	SIZE	SQR IN	BPH	SIZE	SQR IN	BPH	SIZE	SQR IN	BPH
6"	36	2,520	12"	144	10,080	18"	324	22,680	24"	576	40,320
8"	64	4,480	14"	196	13,720	20"	400	28,000	30"	900	63,000
10"	100	7,000	16"	256	17,920	22"	484	33,880	36"	1296	90,720

CONTACT PREMIER COMPONENTS FOR STAINLESS STEEL PRICING.
SEE PAGE 28 FOR SPOUT VELOCITY RECOMMENDATIONS.

SQUARE SPOUTING - SEAM WELDED & REMOVABLE LID STYLE