

3M™ DBI-SALA® Lad-Saf™ FLEXIBLE CABLE VERTICAL SAFETY SYSTEMS



2-User Ladder System and Cable

Cable Length	20 ft	30 ft	40 ft	50 ft	60 ft	70 ft	80 ft	90 ft	100 ft	*110 ft	*120 ft
Number of Guides Included	0	1	1	1	2	2	2	3	3	4	5
GALVANIZED STEEL:											
6116612: Rung, 2 User										6116631	6116631
6104XXX: 1x7 Swaged, 3/8"										6116612	6116612
6100400: Cable Guide for fixed ladder 1 per 30'										6104110	6104120
										6100400	6100400
	6118020	6118030	6118040	6118050	6118060	6118070	6118080	6118090	6118100	6160054	6160054
Price Each	*	*	*	*	*	*	*	*	*	*	*
STAINLESS STEEL:											
6116613: Rung, 2 User										6116631	6116631
6105XXX: 1x7 Swaged, 3/8"										6116612	6116612
6100457: Cable Guide for fixed ladder 1 per 30'										6104110	6104120
										6100400	6100400
	6119020	6119030	6119040	6119050	6119060	6119070	6119080	6119090	6119100	6160054	6160054
Price Each	*	*	*	*	*	*	*	*	*	*	*

*Cable lengths over 100' all part numbers listed are required to make up the kit. One guide every 20 - 30 ft is recommended by the manufacturer.



Pre-swaged cable at desired length

First 4 numbers in SKU represent the cable type, last 3 numbers represent cable length in feet.

Part #	6104XXX	6105XXX	6106XXX	6107XXX
Diameter	3/8 in (9.5 mm)	3/8 in (9.5 mm)	3/8 in (9.5 mm)	3/8 in (9.5 mm)
Strand	1 X 7	1 X 7	7 X 19	7 X 19
Steel	Galvanized	Stainless	Galvanized	Stainless
Preformed	Left, Regular Lay	Left, Regular Lay	Right, Regular Lay	Right, Regular Lay
Compliance	RR-W-410	RR-W-410	RR-W-410	RR-W-410
Breaking strength	15,400 lbs. minimum	18,000 lbs. minimum	14,400 lbs. minimum	12,000 lbs. minimum
Sold in 10' sections	call for pricing	call for pricing	call for pricing	call for pricing

Last three numbers of part # is the length of cable (example: for XXX use 010 which would equal 10' length)

Lifeline cable offered in: *10-100 ft. in 5ft. Increments
*100-200ft. in 10ft. Increments
*Over 200 ft. in 20 ft. Increments

Top & Bottom Bracket System (both brackets included)

Application	User	Material	Part#	Price Each
Rung	2 User	Galvanized Steel	6116631 (6116612)	*
Rung	2 User	Stainless Steel	6116632 (6116613)	*
Rung	4 User	Galvanized Steel	6116633 (6116614)	*
Wood Pole	2 User	Galvanized Steel	6116635 (6116616)	*
Monopole	4 User	Galvanized Steel	6116634 (6116615)	*
Climb Extension	2 User	Galvanized Steel	6116636 (6116617)	*
Telescoping Extension	4 User	Galvanized Steel	6116618	*

6160054
Cable Sleeve
with
Carabiner



Cable Guides as needed (recommended every 20-40 feet)

Application(s)	Type	Material	Part #	Price Each
Ladder	Straight Guide	Galvanized Steel	6100400	*
Ladder	Straight Guide	Stainless Steel	6100457	*
Ladder	L Guide	Stainless Steel	6100513	*
Ladder	Straight Guide	Galvanized Steel	6100530	*
Telescoping & Extension	Straight Guide	Stainless Steel	6100401	*
Monopole	L Guide	Galvanized Steel	6100515	*
Wood Pole	Straight Guide	Stainless Steel	6100140	*

3M Fall Protection Delta Cross-Over Style Climbing Harness 1102010



3M Fall Production Business Harness, Series: Delta™, Universal, 420 lb, Repel™ Polyester Strap, Fastening Method: Pass-Thru Leg Strap, D-Ring Back and Front, Crossover, Steel/E-Coat/Aluminum/Stainless Steel Hardware, Yellow/Navy, Zinc Plated

Hollow Rung ladder supports may be required for additional support.
Contact Premier Components for more Information.